

SUPPLEMENTAL MATERIAL FOR

A NEW VIEW OF SEISMICITY UNDER ETNA VOLCANO, ITALY, 2014-2023 FROM MULTI-SCALE HIGH-PRECISION EARTHQUAKE RELOCATIONS

Anthony Lomax¹, Tiziana Tuvè², Elisabetta Giampiccolo²,
Ornella Cocina²

¹ ALomax Scientific, Mouans-Sartoux, France

² INGV, Sezione di Catania – Osservatorio Etneo. Piazza Roma, 2 – 95125, Catania, Italy

The Supplementary Material includes:

- 1) This text file with **Supplementary Figures S1-S6**.
- 2) **Supplementary File S1 (File_S1_catalog_config_run.zip)** – An archive file containing the full NLL-SSST-coherence relocation catalog in NLL-hypocenter (20240724A_Etna_Seismicity_2014-2023_INGV-OE_NLL-SC.hyp) and CSV (20240724A_Etna_Seismicity_2014-2023_INGV-OE_NLL-SC.csv) formats, as well as metadata and configuration files used to run the NLL-SSST-coherence relocations presented in this study. This archive and a stand-alone copy of 20240724A_Etna_Seismicity_2014-2023_INGV-OE_NLL-SC.csv are both available at <https://doi.org/10.5281/zenodo.13862396>.
- 3) **Movie_S1_Etna_Seismicity_INGV-OE_NLL-SC.mp4** and **Movie_S2_Etna_Seismicity_INGV-OE_NLL-SC.mp4** – 3D animations from different viewpoints of the NLL-SSST-coherence relocations presented in this study.




Figure S1. Initial P-wave velocity model used for NLL-SSST-coherence relocation. Initial NLL relocations are done with the piecewise-linear smooth model Etna1Dsmooth, derived from the Etna1D model (Hirn et al., 1991), using $V_p/V_s = 1.70$ to determine S-wave velocity. The Etna1Dsmooth model is tabulated in the configuration file Etna_2024_Etna1Dsmooth.in included in Supplementary File S1.




Figure S2. Initial NLL locations for 2014-2023 seismicity at Mt. Etna. The full set of 15199 expectation hypocenters for all available events are shown, with other map elements as in Fig. 2 in the main text.




Figure S3. Final NLL-SSST relocations for 2014-2023 seismicity at Mt. Etna. Expectation hypocenters for all available events are shown, with other map elements as in Fig. 2 in the main text.




Figure S4. Final NLL-SSST-coherence relocations for 2014-2023 seismicity at Mt. Etna. Expectation hypocenters for all available events are shown, with other map elements as in Fig. 2 in the main text.




Figure S5. INGV-OE RCSC catalog locations for 2014–2023 seismicity at Mt. Etna. 15687 hypocenters are shown, with other map elements as in Fig. 2 in the main text.

Etna Seismicity 2014-2023 INGV-OE NLL-SC Catalog (15199 events)




Figure S6. Statistics and histograms for all, final NLL-SSST-coherence relocations for 2014-2023 seismicity at Mt. Etna. Mamp = INGV_OE catalog magnitude; expect_z = expectation hypocenter depth; Nphs = number of phases used; Gap = maximum azimuth gap; Dist = distance to closest station; RMS = root-mean-square of (posterior) weighted phase residuals; errH = standard error in epicenter; errZ = standard error in depth; EllipsoidLen3 = length of semi-major axis of 68% x, y, z confidence ellipsoid.

References

Hirn, A., A. Nercessian, M. Sapin, F. Ferrucci et al. (1991). Seismic heterogeneity of Mt Etna: structure and activity, *Geophys. J. Int.*, 105, 139-153, doi:10.1111/j.1365-246X.1991.tb03450.x.